



ClimaGrün

# Product data sheet

Item number: 201040

## Inspection Chamber CG-KSDE 40 h5

for use above roof drains on extensive and intensive roof areas with pressure drainage systems



Technical data	
<b>Material</b>	PP (Polypropylene) with Anti-UV & Stainless Steel
<b>Color</b>	Anthracite & Natural Stainless Steel
<b>Dimensions</b>	ca. 400 x 400 x 60 mm
<b>Weight</b>	approx. 5.3 kg
<b>UV-Resistant</b>	yes
<b>Inspection Chamber Lid</b>	Durable and lockable lid, chamber base opening
<b>Chamber Base Opening</b>	approx. 31 cm
<b>Processing</b>	Connect the sidewalls and click into the base part, place and secure the lid with screws.
<b>Application Area:</b>	For use over drainage outlets in extensive and intensive green roof systems.
<b>Packaging</b>	Approx. 36 x 41 x 41 cm carton
<b>Quantity</b>	One carton contains 6 inspection chambers, each consisting of a base plate, 4 sidewalls, and a lid.
<b>Weight per Carton</b>	approx. 31,8 kg
<b>Storage</b>	Dry storage only

### Tender Text Proposal:

ClimaGrün Inspection Chamber with Stainless Steel Lid CG-KSDE 40 h5, designed for use above roof drains on extensive and intensive roof areas with pressure drainage systems, with the following specifications: Material PP (Polypropylene) & stainless steel, color anthracite & natural stainless steel, dimensions 400 x 400 x 60 mm, weight approx. 5.3 kg, UV-resistant, chamber lid durable and lockable, chamber base opening approx. 31 cm, deliver and install professionally

© ClimaGrün GmbH – Subject to technical changes and printing errors – As of 18.12.2024.