



ClimaGrün

Product data sheet

Item number: 201070

Downpipe Inspection Chamber CG-FKS 40 h2O

for the drainage of water from downpipes with vertical outlets into retention levels



Technical data	
Material	Stainless Steel
Color	Natural Stainless Steel
Dimensions	Approx. 400 x 400 x 205 mm, material thickness 1.5 mm
Weight	approx. 4.8 kg
UV-Resistant	yes
intermediate floor	removable intermediate floor made of perforated sheet metal 5 mm
Chamber Base Opening	approx. 39 x 39 cm
Processing	chamber delivered ready for us
Application Area	for the drainage of water from downpipes with vertical outlets into retention levels
Packaging	Approx. 50 x 55 x 55 cm carton
Quantity	One carton contains 2 inspection chambers, consisting of a chamber, lid, and screws.
Weight per Carton	approx. 9,6 kg
Storage	Dry storage only

Tender Text Proposal:

ClimaGrün Downpipe Inspection Chamber CG-FKS 40 h2O, for the drainage of water from downpipes with vertical outlets into retention levels, with the following specifications: Material stainless steel, dimensions 400 x 400 x 205 mm, material thickness 1.5 mm, removable intermediate floor made of perforated sheet metal 5 mm, weight approx. 4.8 kg, UV-resistant, chamber base opening approx. 39 x 39 cm, deliver and install professionally.