



ClimaGrün

Product data sheet

Item number: 551020

Bulk material brick CG-Z 2/10

for pressure-stable backfilling of plastic drainage tiles and draining levelling layer for intensive greening and paved areas



| Technical data | |
|------------------------|---------------------------------|
| Material | Brick |
| Weight dry | approx. 1.000 kg/m ³ |
| Weight water-saturated | approx. 1.300 kg/m ³ |
| max. water capacity | ≥ 28 Vol % |
| Water permeability | ≥ 60-400 mm/min |
| Salt content | ≤ 2,5 g/l |
| pH value | 6,5 - 8,5 |
| Frost resistant | yes |
| Delivery form | in big bag or loose |
| Quantity | Depending on the order volume |

Suggested tender text:

ClimaGruen bulk material brick CG-Z 2/10, for pressure-stable backfilling of plastic drainage plates and draining levelling layer for intensive greening and surfacing areas, supply and install to the naturally compacted layer height of ____ cm.
Material Brick, weight dry approx. 1.000 kg/m³, weight water saturated approx. 1.300 kg/m³, max. water capacity ≥ 28 vol %, water permeability ≥ 60-400 mm/min, salt content ≤ 2,5 g/l, pH value 6,5 - 8,5. The compaction factor is generally approx. 1,1.

© ClimaGrün GmbH – Subject to technical changes and printing errors – status 27.09.2022