



ClimaGrün

Product data sheet

Item number: 201010

Inspection chamber CG-KS 30 h10

for use above roof drains on extensive and intensive roof areas with gravity drainage



Technical data

Material	PP (Polypropylene) with anti-UV
Colour	anthracite
Dimensions	approx. 300 x 300 x 110 mm
Weight	approx. 1,3 kg
UV-resistant	yes
Manhole cover	tread-resistant & closable cover
Manhole bottom opening	approx. 24 cm
Work instruction	Connect side walls and click into the base part, Put on the lid and screw it on
Area of application	For use above drains in extensive and intensive greening systems
Packaging	approx. 41 x 32 x 33 cm cardboard box
Quantity	One cardboard box contains 6 inspection chambers, consisting of a base plate, 4 side walls and a lid
Weight per cardboard box	approx. 8 kg
Storage	Dry

Suggested tender text:

ClimaGrün inspection chamber CG-KS 30 h10 for use above roof drains on extensive and intensive roof areas with gravity drainage, with the following properties:

Material PP (polypropylene), colour anthracite, dimensions 300 x 300 x 110 mm, weight approx. 1,3 kg, UV-resistant, manhole cover tread-resistant & closable, manhole base opening approx. 24 cm, supply and install professionally.